

# Chesapeake Bay Watershed Model Construction Land Use

Guido Yactayo

University of Maryland Center for Environmental Science  
U.S. EPA Chesapeake Bay Program Office

Matt Johnston

University of Maryland Department of Environmental Science and Technology  
CBPO Non-Point Source Data Analyst

April 22, 2014



# CBWM Calibration Construction Land

- About 84,500 acres (2%) of construction in any given calibration year
- Highest unit area sediment load of any landuse
- 16% of the total delivered sediment load from the urban sector



# CBWM Target Loads for Sediment and Nutrients, without ESC Controls


<b>Sediment Targets</b>			
<b>Source</b>	<b>Yield</b>	<b>Unit</b>	<b>Comment</b>
Guy and Ferguson (1962)	39 to 78	ton/ac-yr	
USEPA (2005)	7.2 to 500	ton/ac-yr	
Schueler (1987)	35 to 45	ton/ac-yr	Literature review
<i>CBWM 5.3</i>	<b>40</b>	<b>ton/ac-yr</b>	<i>discounted to <b>24.4 ton/ac-yr</b> to account for estimated exposure and duration of construction phases</i>

<b>Nutrient Targets</b>			
<b>Source</b>	<b>TN (lb/ac-yr)</b>	<b>TP (lb/ac-yr)</b>	<b>Comment</b>
Line and White (2001)	7.2	2.6	Residential
Daniel et al (1979)	12.2 to 49.5	6.7 to 17.9	Residential
<i>Median target selected for CBWM</i>	<b>26.4</b>	<b>8.81</b>	

# Comparison of Edge of Field Sediment Loads By Land Use in the Bay Watershed (CBWM 5.3.2)

Bay Model Land Use Category	Annual EoF Sediment Load (tons/acre/year)
<b>Construction Sites, No ESC Practices</b>	<b>24.4</b>
<b>Construction Sites, with ESC Practices <sup>1</sup></b>	<b>14.6</b>
Degraded Riparian Pasture	14.0
Extractive, Uncontrolled	10.0
Crops, Conventional Till	5.8
Urban Impervious Cover	5.0
Crops, Conservation Till	3.9
Pasture	1.6
Hay	1.5
Urban Pervious Cover	1.2
Forest (un-harvested)	0.3
<p><i>Sources:</i> Table 9-1 and 9.12 in Chesapeake Bay Phase 5.3 Community Watershed Model (EPA CBP, 2011)</p> <p>Note: Application of BMPs can reduce sediment loads as shown above</p> <p><sup>1</sup> ESC practices are assumed to have a 40% removal rate, per the existing CBP-approved removal rate</p>	



# Impervious Cover Change






- USGS employs Landsat imagery to determine how impervious cover can be changed through the watershed.
- Bare construction is not measured with satellite data.
- Assumption: there must be a relationship between new impervious cover and construction acres.

Image courtesy of CBLCM and Peter Claggett, USGS

# Permitted Construction Acres



# Ratios of Permitted Construction to Impervious Change



- Permit
- P532 Construction Landuse (Counties With Permit)
- P532 Construction Landuse (Counties With No Permit)

# Creating a Construction Land Use

- The ratios of permitted acres to impervious acreage change found in the PA and MD data were used to estimate construction acres across the watershed.
- Both statewide and Baywide median ratios were used if permitted construction data was not submitted by a state.

# Adjusting Construction Acreages

- Each year states have the option to either allow their construction acres to be estimated using the CBP ratios, or submit construction acres.
- Construction acres taken from Construction General Permit (CGP) data tracked by the state.
- Submitted construction acres should represent the average, annual, concurrently permitted construction area for a county.

IT'S TIME  
FOR  
ANOTHER...

# GOOD IDEA BAD IDEA

- **Good Idea?** States are able to accurately reflect their own estimates of construction acres in the Watershed Model each year.
- **Bad Idea?** States who report permitted acres now receive 100% coverage of erosion and sediment control practices on these acres.
- **Good Idea?** Annual reporting will continue to improve the CBP's median ratios used to estimate construction lands.
- **Bad Idea?** Permitted acres can vary significantly from year-to-year, making it more difficult for managers and the public to assess the impact of construction on water quality.

# Questions?

